



**TRIGON EVOLUTION
DESPLAZABLE**



Mulcher of hammers, for the elimination of remains of pruning up to 8 cm and maintenance of vegetable mantle. Ideal for the regeneration of meadows and grassland.


Rotor POLSER of 480 mm de diameter.

Excellent results in industrial gardening and maintenance of borders.

CHARACTERISTICS

- Non-wear plate chassis, thickness 10 mm.
- Rotor POLSER of 480 mm of diameter.
- Group SERRAT.
- 3 SPCX side belt transmission.
- Stamped hammers.
- Hammers guaranteed against breakage.
- GIROSTOP System.
- Supports of bearing rotor in steel.
- Oscillating bearings of double row of rollers.
- Front protection curtain.
- Obturations antiwire in rotor.
- Double bearing on rear roller.
- Height-adjustable roller.
- PTO 540 rpm.
- Rear tine retains (optional).
- Rear roller cleaner.
- Steel counter hammers.
- Model built under EC Normative.
- Safety indicators visible to personnel.





System antiwire in rotor



Rotor POLSER



MODEL								
	mm	KW-HP			A	B	C	
T-1400	1400	44 - 60 88 - 120	12	660	1570	1205	950	540
T-1600	1600	48 - 65 88 - 120	12	670	1790	1205	1040	540
T-1800	1800	51 - 70 88 - 120	16	741	1990	1205	1040	540
T-2000	2000	55 - 75 88 - 120	16	795	2190	1205	1040	540
T-2100	2100	59 - 80 88 - 120	16	815	2290	1205	1040	540
T-2300	2300	63 - 85 88 - 120	20	883	2490	1205	1040	540
T-2500	2500	70 - 95 88 - 120	20	1034	2690	1290	1320	540
T-2800	2800	74 - 100 88 - 120	24	1118	2990	1290	1320	540

OPTIONS

- Overriding clutch on sleeve.
- Runners.
- Overriding clutch on transmission.
- FLOTING System
- Front wheels.
- Rear roller.
- Front chains.



Front wheels



Runners



FLOTING System

