



ANGULAR EVOLUTION



Professional mulcher for the maintenance of ways, gutters, borders, channels, etc. for wood up to 8 cm.

Transmission of direct power by means of 3 groups with system of mechanical safety.

Angulation +120° that allows to fold the mulcher on the chassis, with aptitude to work in vertically when the pumping of the way, the tractor inclines us towards the wings.

Angulation -90° that allows to get down the mulcher, when the tractor is inclined to the center of the way.

CHARACTERISTICS

Non-wear plate chassis.

Rotor POLSER of 450 mm. of diameter.

Direct Group Serrat.

Angulation of +120° a -90°.

Stamped hammers.

Hammers guaranteed against breakage.

GIROSTOP System.

Supports of bearing rotor in steel.

Oscillating bearings of double row of rollers.

Front protection curtain.

Double bearing on rear roller.

Height-adjustable rear roller.

PTO 1000 rpm.

Model built under EC Normative.

Safety indicators visible to personnel.





Front preparation (option)



Rotor Polser



System antiwire in rotor



GIROSTOP System

MODEL								
	mm	KW-HP			A	B	C	
T-1600	1600	59 - 80 96 - 130	12	1004	3950	920	842	1000
T-1800	1800	66 - 90 96 - 130	16	1035	4160	920	842	1000
T-2000	2000	74- 100 96 - 130	16	1060	4370	920	842	1000



Angulation +120° -90°

