



DAP EVOLUTION



Mulcher of high range, polyvalent, lateral and later multiuse, for works in agricultural margins, banks, highways, channels, roads and others clears of public works for tractor of 70 - 120 CV. It incorporates safety system into spring in the arm and double valve of safety in the cylinder of elevation.

It has two positions in rear gate. Angulation $+90^\circ$ / -65° .

Rotor POLSER of 450 mm of diameter with hammer of high edge.

CHARACTERISTICS



- Non-wear plate chassis, thickness 8 mm.
- Rotor POLSER of 450 mm. of diameter.
- Group SERRAT.
- 3 SPCX side belt transmission.
- Stamped hammers.
- Hammers guaranteed against breakage.
- GIROSTOP System.
- Supports of bearing rotor in steel.
- Oscillating bearings of double row of rollers.
- Front protection curtain.
- Double bearing on rear roller.
- Height-adjustable rear roller.
- PTO 540 rpm.
- Hydraulic displacement.
- Security valve.
- Accidents insurance.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Hydraulic displacement



Rotor Polser










System antiwire in rotor



Double valve



GIROSTOP System

MODEL									
	mm	KW-HP				A	B	C	
T-1600	1600	51 - 70 88 - 120	12	24	730	1800	1865	1138	540
T-1800	1800	59 - 80 88 - 120	16	28	769	2000	1865	1138	540
T-2000	2000	59 - 80 88 - 120	16	32	800	2200	1865	1138	540
T- 2300	2300	66 - 90 88 - 120	20	40	850	2525	1865	1138	540

OPTIONS

- Homocinetic knot.




Homocinetic knot



Angulation +90° -65°



Ctra. Nacional N-240 km 149,3
22310 Castejón del Puente (Huesca) - Spain
Tfno. (+34) 974 417 830 - Fax. (+34) 974 410 059
www.serrat.es - comercial@serrat.es



The information presented in this catalogue is provided to merely indicative title and is not binding.