



Mulcher manufactured for mini tractors and motorized cultivator of 30 HP, equipped with hammers.

Mulcher designed for the clearing in agriculture and maintenance of green spaces.

Hooking on screwed to the chassis with two positions, giving the possibility to change the situation of the mulcher regarding the axis of the tractor.

CHARACTERISTICS



- Chassis in deformed sheet.
- Rotor POLSER of 340 mm of diameter.
- Group with overriding clutch.
- 2 SPBX side belt transmission.
- Front protection curtain.
- Bearings of the rotor of high speed.
- Double bearing on rear roller.
- Height-adjustable rear roller.
- Positional hooking.
- PTO 540 rpm.
- Model built under EC Normative.
- Safety indicators visible to personnel.



Group









Roller



Hooking positional




Rotor POLSER

| MODEL |  |  |  |  |  | | |  |
|--------|---|---|---|---|--|-----|-----|---|
| | mm | KW-HP | | | A | B | C | |
| T-1000 | 1000 | 11 - 15 26 - 35 | 10 | 158 | 1079 | 734 | 764 | 540 |



Ctra. Nacional N-240 km 149,3
 22310 Castejón del Puente (Huesca) - Spain
 Tfno. (+34) 974 417 830 - Fax. (+34) 974 404 795
 www.serrat.es - comercial@serrat.es



The information presented in this catalogue is provided to merely indicative title and is not binding.